

**AT-49 SERIES****LEAD PACKAGE**
☒ RoHS Compliant ☒ Pb Free
**STANDARD SPECIFICATION**

Items	Parameter	
Frequency Range	A	B
	3.0 ~ 40 MHz	6.0~40 MHz
Mode	Fundamental	
Frequency Tolerance (at.25°C)	±10ppm	
Load Capacitance (CL)	8pF Min.	
Drive Level (DL)	100μW (Typ.)	
Storage Temperature Range	-30 ~ +80°C	
Aging (at 25°C)	±5ppm/year Max.	

FREQUENCY STABILITY OVER OPERATING TEMPERATURE RANGE

Operating Temperature	Stability
-20 ~ +75°C	±10 ppm

EQUIVALENT SERIES RESISTANCE




3.0 ~ 4.2 MHz	4.3 ~ 6.0 MHz	6.1 ~ 10.0 MHz	10.1 ~ 14.0 MHz	14.1 ~ 29.0 MHz	29.1 ~ 40.0 MHz
150Ω Max.	100Ω Max.	60Ω Max.	50Ω Max.	40Ω Max.	40Ω Max.

*For other specification, please contact us.

Packing Unit : 200pcs/Bag.

DIMENSION

Unit:mm



※Lead pitch shall be measured at the root of leads.

Actual Size

